



Stainless Steel 316/1.4408
Stainless Steel 304/1.4308
Carbon Steel /1.0619

NO	PART NAME	MATERIAL		
1	Body	1.0619	1.4308	1.4408
2	Cap	1.0619	1.4308	1.4408
3	Ball	1.4408		
4	Seat	PTFE		
5	Stem	SS 316		
6	Gasket	PTFE		
7	Thrust washer	PTFE		
8	Packing	PTFE		
9	Gland	SS 304		
10	Spring washer	SS 304		
11	Stem nut	SS 304		
12	Locking device	SS 304		
13	Handle	SS 304		
14	Plastic cover	PLASTIC		
15	Bolt	SS 304		
16	Nut	SS 304		

FEATURES

- Face to face dimension: DIN 3202-F4
- Test: EN 12266-1
- With ISO 5211 Mounting pad
- Investment casting body
- Blow-out proof stem
- Full port
- Lever operated
- With lockable device
- Open-Close written on the handle metal

Gaskets : PTFE - Resistant to transformer oil
Temperature Range : -40 °C +220 °C

DN	L	G	H	ØD	ØK	B	N	d
15	110	140	80	95	65	10	4	Ø14
25	125	160	93	115	85	10	4	Ø14
32	130	160	93	140	100	10	4	Ø18
40	140	185	96	150	110	12	4	Ø18
50	150	185	106	165	125	15	4	Ø18
65	170	185	129	185	145	15	4	Ø18
80	180	190	129	200	160	16	8	Ø18
100	190	230	151	220	180	16	8	Ø18

G and H dimensions can be change with customer request

